


Garant

Solid carbide torus cutter, DLC, Ø h6 DC / R1: 8/0,5 mm



Order data

Order number	206230 8/0,5
GTIN	4045197860248
Item class	11X

Description

Version:

Tolerances:

· Corner radius

$R_1 = 0.5$ tolerance ± 0.02 .

$R_1 > 0.5 - 1.5$ tolerance ± 0.03 .

$R_1 > 1.5$ tolerance ± 0.05 .

With the latest generation of **DLC coating sp²**.

Eccentric relief ground, additionally **polish ground** in the flutes for **outstanding chip evacuation** in long-chipping aluminium components.

Note:

NEW GENERATION AVAILABLE! Recommended successor product is No. 206255.

No. of teeth Z: 3

Helix angle: 45 degrees

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 21 mm

Corner radius R_1 : 0.5 mm

Overhang length L_1 incl. recess: 25 mm

Recess $\varnothing D_1$: 7.4 mm

Overall length L: 63 mm

Technical description

Recess $\varnothing D_1$	7.4 mm
Corner radius R_1	0.5 mm

Shank $\varnothing D_s$	8 mm
Balance quality with shank	G 2.5 with HA
Flute length L_c	21 mm
Cutting edge $\varnothing D_c$	8 mm
Feed f_z for copy milling in short-chipping aluminium	0.04 mm
Feed f_z for side milling in short-chipping aluminium	0.04 mm
Overhang length L_1 incl. recess	25 mm
Shank	DIN 6535 HA to h6
No. of teeth Z	3
Overall length L	63 mm
Helix angle	45 degrees
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Type	W
Tolerance nominal \varnothing	h6
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.5xD for side milling
Cutting width a_e for milling operation	0.05xD for copy milling
Through-coolant	no
Shank tolerance	h6
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------