

**Garant**
**Solid carbide end torus cutter HPC, TiAlN, Ø h9 DC: 2 mm**

**Order data**

Order number	206266 2
GTIN	4045197858016
Item class	11X

**Description**
**Version:**

Special centre cutting edge geometry for traverse milling at very high feed rates.

Tolerance: Corner radius  $R_1 = \pm 0.01$  mm.

**Application:**

**For copy and traverse milling** over the full range of hard machining **under HPC/HSC conditions.**

Using special milling strategies **very high rates of metal removal can be achieved.**

**Note:**

**Successor product to No. 206272.**

**Tools can be reground.**

No. of teeth Z: 2

No. of teeth Z: 2

Dimension  $a_{p \max}$  transverse: 0.15 mm

Programming radius: 0.3 mm

Flute length  $L_c$ : 1.5 mm

Overhang length  $L_1$  incl. recess: 13 mm

Recess  $\varnothing D_1$ : 1.7 mm

**Technical description**

Feed $f_z$ in steel $< 900$ N/mm <sup>2</sup>	0.026 mm
No. of teeth Z	2
Dimension $a_{p \max}$ transverse	0.15 mm
Overhang length $L_1$ incl. recess	13 mm
Shank $\varnothing D_s$	6 mm

Overall length L	54 mm
Programming radius	0.3 mm
Recess $\varnothing D_1$	1.7 mm
Cutting edge $\varnothing D_c$	2 mm
Flute length $L_c$	1.5 mm
Setting angle $\kappa$	11 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h9
Helix angle	15 degrees
Direction of infeed	horizontal and oblique
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Shank	DIN 6535 HA to h5
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------