

**Garant**
**Solid carbide end torus cutter HPC, TiAlN, Ø h9 DC: 4 mm**

**Order data**

Order number	206267 4
GTIN	4045197860705
Item class	11X

**Description**
**Version:**

Special centre cutting edge geometry for traverse milling at very high feed rates.

Tolerance: Corner radius  $R_1 = \pm 0.01$  mm.

**Application:**

**For copy and traverse milling** over the full range of hard machining **under HPC/HSC conditions.**

Using special milling strategies **very high rates of metal removal can be achieved.**

**Note:**

**Successor product to No. 206274.**

**Tools can be reground.**

No. of teeth Z: 2

No. of teeth Z: 2

Dimension  $a_{p\ max}$  transverse: 0.25 mm

Programming radius: 0.5 mm

Flute length  $L_c$ : 2.5 mm

Overhang length  $L_1$  incl. recess: 24 mm

Recess  $\varnothing D_1$ : 3.6 mm

**Technical description**

Shank $\varnothing D_s$	6 mm
No. of teeth Z	2
Flute length $L_c$	2.5 mm
Feed $f_z$ in steel < 900 N/mm <sup>2</sup>	0.06 mm
Recess $\varnothing D_1$	3.6 mm

Dimension $a_{p\ max}$ transverse	0.25 mm
Overall length L	85 mm
Overhang length $L_1$ incl. recess	24 mm
Cutting edge $\varnothing D_c$	4 mm
Programming radius	0.5 mm
Setting angle $\kappa$	10.5 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h9
Helix angle	15 degrees
Direction of infeed	horizontal and oblique
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Shank	DIN 6535 HA to h5
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------