

Garant
Solid carbide torus cutter, TiAlN, Ø e8 DC / R1: 16/2,0 mm

Order data

| | |
|--------------|---------------|
| Order number | 206280 16/2,0 |
| GTIN | 4045197124135 |
| Item class | 11X |

Description
Version:

With **double relief ground side clearance angle**.

Tolerance: Corner radius $R_1 = \pm 0.005$ mm.

Application:

Especially for **high speed machining** in **mould and tool making** for **copy milling**. Excellent results when **milling dry**.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 206333.

No. of teeth Z: 4

Helix angle: 30 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 16 mm

Corner radius R_1 : 2 mm

Overhang length L_1 incl. recess: 44 mm

Recess $\varnothing D_1$: 15 mm

Overall length L: 92 mm

Technical description

| | |
|------------------------------------|-------|
| Recess $\varnothing D_1$ | 15 mm |
| Corner radius R_1 | 2 mm |
| Cutting edge $\varnothing D_c$ | 16 mm |
| Overhang length L_1 incl. recess | 44 mm |

| | |
|---|----------------------------------|
| Feed f_z for copy milling in steel < 1100 N/mm ² | 0.062 mm |
| Feed f_z for side milling in steel < 1100 N/mm ² | 0.055 mm |
| No. of teeth Z | 4 |
| Shank $\varnothing D_s$ | 16 mm |
| Flute length L_c | 16 mm |
| Overall length L | 92 mm |
| Shank | DIN 6535 HA to h6 |
| Helix angle | 30 degrees |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | H |
| Tolerance nominal \varnothing | e8 |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | 0.05×D for copy milling |
| Cutting width a_e for milling operation | 0.2×D for side milling |
| Through-coolant | no |
| Shank tolerance | h6 |
| Colour ring | without |
| Type of product | End mill |

Services

| | |
|---|-------------|
| Shank recess Type FRST | 209900 FRST |
| Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm | SZ2025 16 |
| Shank grinding Type HB | 129100 HB |