

Garant
Solid carbide torus cutter, TiAlN, Ø e8 DC / R1: 5/1,0 mm

Order data

Order number	206300 5/1,0
GTIN	4045197124289
Item class	11X

Description
Version:

With **double relief ground side clearance angle**.

Tolerance: Corner radius $R_1 = \pm 0.005$ mm.

Application:

Especially for **high speed machining in mould and tool making for copy milling**. Excellent results when **milling dry**.

Note:

NEW GENERATION AVAILABLE!

Recommended successor product is No. 206335.

No. of teeth Z: 4

Helix angle: 30 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 6 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 40 mm

Recess $\varnothing D_1$: 4.6 mm

Overall length L: 75 mm

Technical description

Recess $\varnothing D_1$	4.6 mm
Feed f_z for side milling in steel < 1100 N/mm ²	0.013 mm
Cutting edge $\varnothing D_c$	5 mm
No. of teeth Z	4

Corner radius R_1	1 mm
Overhang length L_1 incl. recess	40 mm
Feed f_z for copy milling in steel $< 1100 \text{ N/mm}^2$	0.014 mm
Shank $\varnothing D_s$	5 mm
Flute length L_c	6 mm
Overall length L	75 mm
Shank	DIN 6535 HA to h6
Helix angle	30 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.05 \times D$ for copy milling
Cutting width a_e for milling operation	$0.2 \times D$ for side milling
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------