

**Garant**
**Diabolo carbide torus cutter HPC, TiAlN, Ø e8 DC / R1: 16/3,0 mm**

**Order data**

Order number	206342 16/3,0
GTIN	4045197599018
Item class	11X

**Description**
**Version:**
**GARANT Diabolo:**

Special geometry, coating and carbide, specially for hard machining.

Double relief ground side clearance angle.

Tolerance: Corner radius  $R_1 = \pm 0.005 \text{ mm}$ .

No. of teeth Z: 4

Helix angle: 30 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length  $L_c$ : 16 mm

Corner radius  $R_1$ : 3 mm

Overhang length  $L_1$  incl. recess: 92 mm

Recess  $\varnothing D_1$ : 15 mm

Overall length L: 150 mm

**Technical description**

Feed $f_z$ for side milling in steel < 65 HRC	0.09 mm
No. of teeth Z	4
Feed $f_z$ for copy milling in steel < 65 HRC	0.09 mm
Recess $\varnothing D_1$	15 mm
Corner radius $R_1$	3 mm
Overhang length $L_1$ incl. recess	92 mm
Cutting edge $\varnothing D_c$	16 mm

Shank $\varnothing D_s$	16 mm
Flute length $L_c$	16 mm
Overall length $L$	150 mm
Shank	DIN 6535 HA to h6
Helix angle	30 degrees
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal $\varnothing$	e8
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.2×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	red
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank $\varnothing$ tool 16 mm	SZ2025 16
Shank grinding Type HB	129100 HB