

Garant

GARANT Master INOX solid carbide torus cutter HPC DIN 6535 HA, TiAlN, Ø DC / R1: 6/1,5 mm



Order data

Order number	206345 6/1,5
GTIN	4045197852007
Item class	11X

Description

Version:

Dimensions similar to DIN 6527.

HPC milling cutter with **newly developed high-performance coating**.

For **outstanding tool life** and **optimum metal removal rate** in a very wide range of stainless steels.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Advantage:

Greater oxidation resistance and high-temperature hardness.

No. of teeth Z: 4

Helix angle: 40 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 13 mm

Corner radius R_1 : 1.5 mm

Overhang length L_1 incl. recess: 21 mm

Recess Ø D_1 : 5.5 mm

Overall length L: 57 mm

Technical description

Recess Ø D_1	5.5 mm
Feed f_z for side milling in INOX > 900 N/mm ²	0.026 mm
Cutting edge Ø D_c	6 mm
Overhang length L_1 incl. recess	21 mm

No. of teeth Z	4
Corner radius R ₁	1.5 mm
Overall length L	57 mm
Feed f _z for copy milling in stainless steel > 900 N/mm ²	0.032 mm
Flute length L _c	13 mm
Shank Ø D _s	6 mm
Shank	DIN 6535 HA to h6
Helix angle	40 degrees
Series	GARANT Master INOX
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	h10
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a _e for milling operation	0.3×D for side milling
Cutting width a _e for milling operation	0.05×D for copy milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	blue
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------