

**HOLEX**
**HOLEX Pro INOX solid carbide torus cutter HPC DIN 6535 HB, AlCrN, Ø DC / R1: 10/1,5 mm**

**Order data**

Order number	206348 10/1,5
GTIN	4045197859808
Item class	12X

**Description**
**Version:**

Dimensions similar to DIN 6527.

HPC milling cutter with **newly developed high-performance coating**.

For **outstanding tool life** and **optimum metal removal rate** in a very wide range of stainless steels.

For use at **high cutting speeds**, particularly suitable even for steels up to approx. 1100 N/mm<sup>2</sup>.

No. of teeth Z: 4

Helix angle: 35 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L<sub>c</sub>: 22 mm

Corner radius R<sub>1</sub>: 1.5 mm

Overhang length L<sub>1</sub> incl. recess: 30 mm

Recess Ø D<sub>1</sub>: 9.7 mm

Overall length L: 72 mm

**Technical description**

Feed f <sub>z</sub> for copy milling in stainless steel > 900 N/mm <sup>2</sup>	0.053 mm
Shank	DIN 6535 HB to h6
Flute length L <sub>c</sub>	22 mm
No. of teeth Z	4
Shank Ø D <sub>s</sub>	10 mm

Recess $\varnothing D_1$	9.7 mm
Cutting edge $\varnothing D_c$	10 mm
Overhang length $L_1$ incl. recess	30 mm
Feed $f_z$ for side milling in INOX > 900 N/mm <sup>2</sup>	0.043 mm
Corner radius $R_1$	1.5 mm
Overall length $L$	72 mm
Helix angle	35 degrees
Series	HOLEX Pro INOX
Coating	AlCrN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	f8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.3×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	blue
Type of product	End mill