



## HOLEX Pro INOX solid carbide torus cutter HPC DIN 6535 HB, AlCrN, Ø DC / R1: 16/3,0 mm



### Order data

Order number	206348 16/3,0
GTIN	4045197859952
Item class	12X

### Description

#### Version:

Dimensions similar to DIN 6527.

HPC milling cutter with **newly developed high-performance coating**.

For **outstanding tool life** and **optimum metal removal rate** in a very wide range of stainless steels.

For use at **high cutting speeds**, particularly suitable even for steels up to approx. 1100 N/mm<sup>2</sup>.

No. of teeth Z: 4

Helix angle: 35 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L<sub>c</sub>: 36 mm

Corner radius R<sub>1</sub>: 3 mm

Overhang length L<sub>1</sub> incl. recess: 42 mm

Recess Ø D<sub>1</sub>: 15.5 mm

Overall length L: 92 mm

### Technical description

Overhang length L <sub>1</sub> incl. recess	42 mm
Feed f <sub>z</sub> for side milling in INOX > 900 N/mm <sup>2</sup>	0.067 mm
Shank Ø D <sub>s</sub>	16 mm
Recess Ø D <sub>1</sub>	15.5 mm
Feed f <sub>z</sub> for copy milling in stainless steel > 900 N/mm <sup>2</sup>	0.083 mm

No. of teeth Z	4
Corner radius R <sub>1</sub>	3 mm
Cutting edge Ø D <sub>c</sub>	16 mm
Overall length L	92 mm
Flute length L <sub>c</sub>	36 mm
Shank	DIN 6535 HB to h6
Helix angle	35 degrees
Series	HOLEX Pro INOX
Coating	AlCrN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	f8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a <sub>e</sub> for milling operation	0.05×D for copy milling
Cutting width a <sub>e</sub> for milling operation	0.3×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	blue
Type of product	End mill

## Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank Ø tool 16 mm

SZ2025 16