



## HOLEX Pro INOX solid carbide torus cutter HPC DIN 6535 HB, AlCrN, Ø DC / R1: 4/0,4 mm



### Order data

Order number	206348 4/0,4
GTIN	4045197854780
Item class	12X

### Description

#### Version:

Dimensions similar to DIN 6527.

HPC milling cutter with **newly developed high-performance coating**.

For **outstanding tool life** and **optimum metal removal rate** in a very wide range of stainless steels.

For use at **high cutting speeds**, particularly suitable even for steels up to approx. 1100 N/mm<sup>2</sup>.

No. of teeth Z: 4

Helix angle: 35 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L<sub>c</sub>: 11 mm

Corner radius R<sub>1</sub>: 0.4 mm

Overhang length L<sub>1</sub> incl. recess: 17 mm

Recess Ø D<sub>1</sub>: 3.8 mm

Overall length L: 57 mm

### Technical description

Cutting edge Ø D <sub>c</sub>	4 mm
Flute length L <sub>c</sub>	11 mm
Feed f <sub>z</sub> for side milling in INOX > 900 N/mm <sup>2</sup>	0.016 mm
Overhang length L <sub>1</sub> incl. recess	17 mm
Shank Ø D <sub>s</sub>	6 mm

Shank	DIN 6535 HB to h6
Feed $f_z$ for copy milling in stainless steel $> 900 \text{ N/mm}^2$	0.02 mm
No. of teeth Z	4
Corner radius $R_1$	0.4 mm
Recess $\varnothing D_1$	3.8 mm
Overall length L	57 mm
Helix angle	35 degrees
Series	HOLEX Pro INOX
Coating	AlCrN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	f8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	$0.05 \times D$ for copy milling
Cutting width $a_e$ for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	blue
Type of product	End mill