


**Solid carbide torus cutter HPC DIN 6535 HB, TiSi, Ø DC / R1: 20/2,0 mm**

**Order data**

Order number	206353 20/2,0
GTIN	4045197540393
Item class	12X

**Description**
**Version:**

Dimensions to factory standard and 35° spiral.

**Special TiSi coating.**

With balancing speed G 2.5.

**Note:**
**NEW GENERATION AVAILABLE!**

**Recommended successor product is No. 206348**

No. of teeth Z: 4

Helix angle: 35 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length  $L_c$ : 41 mm

Corner radius  $R_1$ : 2 mm

Overhang length  $L_1$  incl. recess: 52 mm

Recess Ø  $D_1$ : 19.5 mm

Overall length L: 104 mm

**Technical description**

Overhang length $L_1$ incl. recess	52 mm
No. of teeth Z	4
Feed $f_z$ for side milling in INOX > 900 N/mm <sup>2</sup>	0.085 mm
Cutting edge Ø $D_c$	20 mm
Feed $f_z$ for copy milling in stainless steel > 900 N/mm <sup>2</sup>	0.105 mm

Recess $\varnothing D_1$	19.5 mm
Corner radius $R_1$	2 mm
Shank $\varnothing D_s$	20 mm
Flute length $L_c$	41 mm
Overall length $L$	104 mm
Shank	DIN 6535 HB to h6
Helix angle	35 degrees
Coating	TiSi
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	f8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.3×D for side milling
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	blue
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank $\varnothing$ tool 20 mm	SZ2025 20