

## Garant

### GARANT Master Steel solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 10/2,0 mm



#### Order data

Order number	206354 10/2,0
GTIN	4045197778673
Item class	11X

#### Description

##### Version:

Tolerance: Corner radius  $R_1 = \pm 0.01$  mm.

##### Advantage:

HPC milling cutters with various corner radii for all radial transitions. Optimised flute form, eccentric relief ground, wide chip space.

No. of teeth Z: 4

Helix angle: 38 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length  $L_c$ : 22 mm

Corner radius  $R_1$ : 2 mm

Overhang length  $L_1$  incl. recess: 30 mm

Recess  $\varnothing D_1$ : 9.8 mm

Overall length L: 72 mm

#### Technical description

Recess $\varnothing D_1$	9.8 mm
Flute length $L_c$	22 mm
Overall length L	72 mm
Cutting edge $\varnothing D_c$	10 mm
No. of teeth Z	4
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.08 mm

Overhang length $L_1$ incl. recess	30 mm
Corner radius $R_1$	2 mm
Shank $\varnothing D_s$	10 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.06 mm
Shank	DIN 6535 HB to h6
Helix angle	38 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal $\varnothing$	f8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill