

Garant
GARANT Master Steel solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 10/3,0 mm

Order data

| | |
|--------------|---------------|
| Order number | 206354 10/3,0 |
| GTIN | 4045197778697 |
| Item class | 11X |

Description
Version:

Tolerance: Corner radius $R_1 = \pm 0.01$ mm.

Advantage:

HPC milling cutters with various corner radii for all radial transitions.
Optimised flute form, eccentric relief ground, wide chip space.

No. of teeth Z: 4

Helix angle: 38 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 22 mm

Corner radius R_1 : 3 mm

Overhang length L_1 incl. recess: 30 mm

Recess $\varnothing D_1$: 9.8 mm

Overall length L: 72 mm

Technical description

| | |
|--|---------|
| Cutting edge $\varnothing D_c$ | 10 mm |
| No. of teeth Z | 4 |
| Overall length L | 72 mm |
| Feed f_z for side milling in steel < 900 N/mm ² | 0.08 mm |
| Shank $\varnothing D_s$ | 10 mm |
| Recess $\varnothing D_1$ | 9.8 mm |

| | |
|--|--------------------------------------|
| Corner radius R_1 | 3 mm |
| Overhang length L_1 incl. recess | 30 mm |
| Flute length L_c | 22 mm |
| Feed f_z for slot milling in steel < 900 N/mm ² | 0.06 mm |
| Shank | DIN 6535 HB to h6 |
| Helix angle | 38 degrees |
| Series | GARANT Master Steel |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Standard | DIN 6527 |
| Type | N |
| Tolerance nominal \varnothing | f8 |
| Helix angle characteristic | unequal spacing |
| Spacing of the cutters | unequal spacing |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | Full slot cutting depth $1 \times D$ |
| Cutting width a_e for milling operation | $0.3 \times D$ for side milling |
| Through-coolant | no |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | End mill |