


**HOLEX Pro Steel solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 10/0,5 mm**

**Order data**

Order number	206357 10/0,5
GTIN	4045197770400
Item class	12X

**Description**
**Version:**

Tolerance: Corner radius  $R_1 = \pm 0.03$  mm.

**Advantage:**

HPC milling cutters will with various corner radii for all radial transitions.

Optimised flute form, eccentric relief ground, wide chip space.

No. of teeth Z: 4

Helix angle: 38 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length  $L_c$ : 22 mm

Corner radius  $R_1$ : 0.5 mm

Overhang length  $L_1$  incl. recess: 32 mm

Recess Ø  $D_1$ : 9.5 mm

Overall length L: 72 mm

**Technical description**

Shank Ø $D_s$	10 mm
Corner radius $R_1$	0.5 mm
No. of teeth Z	4
Recess Ø $D_1$	9.5 mm
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.08 mm
Cutting edge Ø $D_c$	10 mm
Overall length L	72 mm

Overhang length $L_1$ incl. recess	32 mm
Flute length $L_c$	22 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.06 mm
Shank	DIN 6535 HB to h6
Helix angle	38 degrees
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	0 / -0.03
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill