


HOLEX Pro Steel solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 12/1,5 mm

Order data

| | |
|--------------|---------------|
| Order number | 206357 12/1,5 |
| GTIN | 4045197770462 |
| Item class | 12X |

Description
Version:

Tolerance: Corner radius $R_1 = \pm 0.03$ mm.

Advantage:

HPC milling cutters will with various corner radii for all radial transitions.

Optimised flute form, eccentric relief ground, wide chip space.

No. of teeth Z: 4

Helix angle: 38 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 26 mm

Corner radius R_1 : 1.5 mm

Overhang length L_1 incl. recess: 38 mm

Recess Ø D_1 : 11.5 mm

Overall length L: 83 mm

Technical description

| | |
|--|---------|
| Cutting edge Ø D_c | 12 mm |
| Corner radius R_1 | 1.5 mm |
| Overhang length L_1 incl. recess | 38 mm |
| Recess Ø D_1 | 11.5 mm |
| Flute length L_c | 26 mm |
| Feed f_z for side milling in steel < 900 N/mm ² | 0.09 mm |
| No. of teeth Z | 4 |

| | |
|--|--------------------------------------|
| Shank $\varnothing D_s$ | 12 mm |
| Overall length L | 83 mm |
| Feed f_z for slot milling in steel < 900 N/mm ² | 0.07 mm |
| Shank | DIN 6535 HB to h6 |
| Helix angle | 38 degrees |
| Series | HOLEX Pro Steel |
| Coating | TiAlN |
| Tool material | solid carbide |
| Standard | Manufacturer's standard |
| Type | N |
| Tolerance nominal \varnothing | 0 / -0.03 |
| Helix angle characteristic | unequal spacing |
| Spacing of the cutters | unequal spacing |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | Full slot cutting depth $1 \times D$ |
| Cutting width a_e for milling operation | Full slot cutting depth $1 \times D$ |
| Through-coolant | no |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | End mill |

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 12 mm

SZ2025 12