


HOLEX Pro Steel solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 5/1,0 mm

Order data

| | |
|--------------|---------------|
| Order number | 206357 5/1,0 |
| GTIN | 4045197770578 |
| Item class | 12X |

Description
Version:

Tolerance: Corner radius $R_1 = \pm 0.03$ mm.

Advantage:

HPC milling cutters will with various corner radii for all radial transitions.

Optimised flute form, eccentric relief ground, wide chip space.

No. of teeth Z: 4

Helix angle: 38 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 13 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 17 mm

Recess Ø D_1 : 4.8 mm

Overall length L: 57 mm

Technical description

| | |
|--|---------|
| Overhang length L_1 incl. recess | 17 mm |
| Overall length L | 57 mm |
| No. of teeth Z | 4 |
| Shank Ø D_s | 6 mm |
| Corner radius R_1 | 1 mm |
| Recess Ø D_1 | 4.8 mm |
| Feed f_z for side milling in steel < 900 N/mm ² | 0.04 mm |

| | |
|--|--------------------------------------|
| Cutting edge $\varnothing D_c$ | 5 mm |
| Flute length L_c | 13 mm |
| Feed f_z for slot milling in steel < 900 N/mm ² | 0.03 mm |
| Shank | DIN 6535 HB to h6 |
| Helix angle | 38 degrees |
| Series | HOLEX Pro Steel |
| Coating | TiAlN |
| Tool material | solid carbide |
| Standard | Manufacturer's standard |
| Type | N |
| Tolerance nominal \varnothing | 0 / -0.03 |
| Helix angle characteristic | unequal spacing |
| Spacing of the cutters | unequal spacing |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | Full slot cutting depth $1 \times D$ |
| Cutting width a_e for milling operation | Full slot cutting depth $1 \times D$ |
| Through-coolant | no |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | End mill |