


**Garant**
**Diabolo solid carbide torus cutter HPC, TiAlN, Ø e8 DC / R1: 16/2,0 mm**

**Order data**

Order number	206372 16/2,0
GTIN	4045197599230
Item class	11X

**Description**
**Version:**
**GARANT Diabolo:**

Special geometry, coating and carbide for hard machining.

Tolerance: Corner radius  $R_1 = \pm 0.005 \text{ mm}$ .

Without dynamic twist pitch.

Without dynamic twist pitch.

No. of teeth Z: 6

Helix angle: 50 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length  $L_c$ : 16 mm

Corner radius  $R_1$ : 2 mm

Overhang length  $L_1$  incl. recess: 44 mm

Recess  $\varnothing D_1$ : 15 mm

Overall length L: 92 mm

**Technical description**

Recess $\varnothing D_1$	15 mm
No. of teeth Z	6
Cutting edge $\varnothing D_c$	16 mm
Feed $f_z$ for copy milling in steel < 65 HRC	0.09 mm
Corner radius $R_1$	2 mm
Overhang length $L_1$ incl. recess	44 mm

Shank $\varnothing D_s$	16 mm
Flute length $L_c$	16 mm
Overall length $L$	92 mm
Shank	DIN 6535 HA to h6
Helix angle	50 degrees
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal $\varnothing$	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.05×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	red
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank $\varnothing$ tool 16 mm	SZ2025 16
Shank grinding Type HB	129100 HB