

Garant
Diabolo solid carbide torus cutter HPC, TiAlN, Ø e8 DC / R1: 16/3,0 mm

Order data

Order number	206372 16/3,0
GTIN	4045197599247
Item class	11X

Description
Version:
GARANT Diabolo:

Special geometry, coating and carbide for hard machining.

Tolerance: Corner radius $R_1 = \pm 0.005 \text{ mm}$.

Without dynamic twist pitch.

Without dynamic twist pitch.

No. of teeth Z: 6

Helix angle: 50 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c : 16 mm

Corner radius R_1 : 3 mm

Overhang length L_1 incl. recess: 44 mm

Recess $\varnothing D_1$: 15 mm

Overall length L: 92 mm

Technical description

Corner radius R_1	3 mm
Recess $\varnothing D_1$	15 mm
Overhang length L_1 incl. recess	44 mm
Feed f_z for copy milling in steel < 65 HRC	0.09 mm
Cutting edge $\varnothing D_c$	16 mm
No. of teeth Z	6

Shank $\varnothing D_s$	16 mm
Flute length L_c	16 mm
Overall length L	92 mm
Shank	DIN 6535 HA to h6
Helix angle	50 degrees
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Cutting width a_e for milling operation	0.05×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	red
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16
Shank grinding Type HB	129100 HB