

**Garant**
**Solid carbide copy slot drill, DLC, Ø DC × L1: 0,1X0,3 mm**

**Order data**

Order number	207023 0,1X0,3
GTIN	4045197912343
Item class	11X

**Description**
**Version:**

With **advanced DLC sp<sup>2</sup> coating**. For the **highest demands regarding performance and precision in aluminium materials**. **Extremely tight tolerances** ensure maximum accuracy. Double-relief ground with 2 chamfers hollow ground.

Recess angle  $\alpha = 16^\circ$ .

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø:  $D_1 = 0 / -0.01$  mm.**

**Note:**

At greater tool overhang lengths, use a reduced value for  $a_p$ !

values for:

copying:  $a_p = 0.25 \times D \times a_{p, \text{korr}}$

**To calculate the feed rate  $vf$  please use the actual speed of the machine (the maximum possible speed)!**

e.g:  $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

No. of teeth Z: 2

Helix angle: 25 degrees

No. of teeth Z: 2

Flute length  $L_c$ : 0.08 mm

Corner radius  $R_1$ : 0.05 mm

Overhang length  $L_1$  incl. recess: 0.3 mm

Recess Ø  $D_1$ : 0.08 mm

Overall length L: 45 mm

**Technical description**

Recess Ø $D_1$	0.08 mm
----------------	---------

Cutting edge $\varnothing D_c$	0.1 mm
Feed $f_z$ for copy milling in cast aluminium	0.012 mm
Shank $\varnothing D_s$	4 mm
Overhang length $L_1$ incl. recess	0.3 mm
Flute length $L_c$	0.08 mm
Overall length $L$	45 mm
No. of teeth $Z$	2
Corner radius $R_1$	0.05 mm
Helix angle	25 degrees
Correction factor $a_{p,corr}$	1
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal $\varnothing$	0 / -0.005
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	yellow
Type of product	End mill