

Garant
Solid carbide copy slot drill, DLC, Ø DC × L1: 0,4X1,5 mm

Order data

| | |
|--------------|----------------|
| Order number | 207023 0,4X1,5 |
| GTIN | 4062406188047 |
| Item class | 11X |

Description
Version:

With **advanced DLC sp² coating**. For the **highest demands regarding performance and precision in aluminium materials**. **Extremely tight tolerances** ensure maximum accuracy. Double-relief ground with 2 chamfers hollow ground.

Recess angle $\alpha = 16^\circ$.

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø: D₁ = 0 / -0.01 mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p!
values for:

copying: $a_p = 0.25 \times D \times a_{p, \text{korr}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!

e.g: $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

No. of teeth Z: 2

Helix angle: 25 degrees

No. of teeth Z: 2

Flute length L_c: 0.32 mm

Overhang length L₁ incl. recess: 1.5 mm

Recess Ø D₁: 0.37 mm

Overall length L: 45 mm

Shank Ø D_s: 4 mm

Technical description

| | |
|----------------|---|
| No. of teeth Z | 2 |
|----------------|---|

| | |
|---|----------------------------------|
| Recess $\varnothing D_1$ | 0.37 mm |
| Flute length L_c | 0.32 mm |
| Overall length L | 45 mm |
| Helix angle | 25 degrees |
| Shank $\varnothing D_s$ | 4 mm |
| Overhang length L_1 incl. recess | 1.5 mm |
| Cutting edge $\varnothing D_c$ | 0.4 mm |
| Radius R | 0.2 mm |
| Coating | DLC |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | W |
| Tolerance nominal \varnothing | 0 / -0.005 |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | 0.05×D for copy milling |
| Shank | DIN 6535 HA to h5 |
| Through-coolant | no |
| Colour ring | yellow |
| Type of product | End mill |