

**Garant**
**Solid carbide ball nose slot drill, uncoated, Ø DC: 2 mm**

**Order data**

Order number	207106 2
GTIN	4045197540447
Item class	11X

**Description**

Solid carbide ball nose slot drill 2 mm  
 No. of teeth Z: 2  
 Helix angle: 30 degrees  
 No. of teeth Z: 2  
 Flute length  $L_c$ : 2 mm  
 Overhang length  $L_1$  incl. recess: 6 mm  
 Recess Ø  $D_1$ : 1.92 mm  
 Overall length L: 50 mm  
 Shank Ø  $D_s$ : 6 mm

**Technical description**

No. of teeth Z	2
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.011 mm
Overhang length $L_1$ incl. recess	6 mm
Feed $f_z$ for copy milling in steel < 900 N/mm <sup>2</sup>	0.013 mm
Recess Ø $D_1$	1.92 mm
Cutting edge Ø $D_c$	2 mm
Shank Ø $D_s$	6 mm
Overall length L	50 mm
Flute length $L_c$	2 mm
Helix angle	30 degrees
Radius R	1 mm

Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.05×D for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	without
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------