


Solid carbide ball nose slot drill, TiAlN, Ø DC: 10 mm

Order data

Order number	207125 10
GTIN	4045197126382
Item class	12X

Description

Solid carbide ball nose slot drill 10 mm No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L_c : 14 mm

Overall length L: 66 mm

Shank Ø D_s : 10 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.06 mm

Feed f_z for copy milling in steel < 900 N/mm²: 0.068 mm

Technical description

No. of teeth Z	2
Feed f_z for copy milling in steel < 900 N/mm ²	0.068 mm
Cutting edge Ø D_c	10 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.06 mm
Shank Ø D_s	10 mm
Overall length L	66 mm
Flute length L_c	14 mm
Helix angle	30 degrees
Radius R	5 mm
Coating	TiAlN

Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h10
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Cutting width a_e for milling operation	0.05×D for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB