

Garant
Solid carbide ball nose slot drill 260°, TiAlN, Ø DC: 2 mm

Order data

Order number	207176 2
GTIN	4045197858320
Item class	11X

Description
Version:

Exact **radius form without profile distortion.**

Double relief ground side clearance angle.

Tolerance: Radius contour = **±0.01 mm.**

With enclosed angle **260°**. Size nominal Ø: **D_c = 0 / -0.01 mm.**

Note:

Straight ground recess.

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Cutter length l_c: 1.7 mm

Overhang length L₁ incl. recess: 10 mm

Recess Ø D₁: 1.4 mm

Overall length L: 58 mm

Shank Ø D_s: 6 mm

Technical description

Shank Ø D _s	6 mm
Cutter length l _c	1.7 mm
Recess Ø D ₁	1.4 mm
Cutting edge Ø D _c	2 mm
No. of teeth Z	2
Overall length L	58 mm
Overhang length L ₁ incl. recess	10 mm

Feed f_z for copy milling in steel < 1100 N/mm ²	0.01 mm
Helix angle	30 degrees
Radius R	1 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.03×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------