

Garant
Solid carbide ball nose slot drill 260°, TiAlN, Ø DC: 6 mm

Order data

Order number	207176 6
GTIN	4045197858368
Item class	11X

Description
Version:

Exact **radius form without profile distortion.**

Double relief ground side clearance angle.

Tolerance: Radius contour = **±0.01 mm.**

With enclosed angle **260°**. Size nominal Ø: **D_c = -0.01 / -0.025 mm.**

Note:

Ground recess after cutter length L_c is conically increasing.

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Cutter length l_c: 5.2 mm

Overhang length L₁ incl. recess: 30 mm

Recess Ø D₁: 4.2 mm

Overall length L: 100 mm

Shank Ø D_s: 6 mm

Technical description

Overhang length L ₁ incl. recess	30 mm
Overall length L	100 mm
Feed f _z for copy milling in steel < 1100 N/mm ²	0.044 mm
Recess Ø D ₁	4.2 mm
Cutter length l _c	5.2 mm
Cutting edge Ø D _c	6 mm

No. of teeth Z	2
Shank $\varnothing D_s$	6 mm
Helix angle	30 degrees
Radius R	3 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.03×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------