

**Garant**
**Solid carbide ball nose slot drill 260°, TiAlN, Ø DC: 8 mm**

**Order data**

Order number	207176 8
GTIN	4045197858375
Item class	11X

**Description**
**Version:**

Exact **radius form without profile distortion.**

Double relief ground side clearance angle.

Tolerance: Radius contour = **±0.01 mm.**

With enclosed angle **260°**. Size nominal Ø: **D<sub>c</sub> = -0.01 / -0.025 mm.**

**Note:**

Ground recess after cutter length L<sub>c</sub> is conically increasing.

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Cutter length l<sub>c</sub>: 7 mm

Overhang length L<sub>1</sub> incl. recess: 40 mm

Recess Ø D<sub>1</sub>: 5.6 mm

Overall length L: 100 mm

Shank Ø D<sub>s</sub>: 8 mm

**Technical description**

Shank Ø D <sub>s</sub>	8 mm
Overhang length L <sub>1</sub> incl. recess	40 mm
Recess Ø D <sub>1</sub>	5.6 mm
Overall length L	100 mm
No. of teeth Z	2
Cutting edge Ø D <sub>c</sub>	8 mm

Feed $f_z$ for copy milling in steel < 1100 N/mm <sup>2</sup>	0.052 mm
Cutter length $l_c$	7 mm
Helix angle	30 degrees
Radius R	4 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.03×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	without
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------