

Garant
Solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / D S: 5 mm

Order data

Order number	207240 5
GTIN	4045197127143
Item class	11X

Description
Version:

Precision ground for very high accuracy requirements.

Tolerance: Radius contour = ± 0.005 mm.

Note:

Recommended successor product is No. 207242.

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L_c : 9 mm

Overall length L: 54 mm

Shank $\varnothing D_s$: 5 mm

Feed f_z for side milling in steel < 1100 N/mm²: 0.032 mm

Feed f_z for copy milling in steel < 1100 N/mm²: 0.037 mm

Technical description

Feed f_z for side milling in steel < 1100 N/mm ²	0.032 mm
Cutting edge $\varnothing D_c$	5 mm
No. of teeth Z	2
Feed f_z for copy milling in steel < 1100 N/mm ²	0.037 mm
Shank $\varnothing D_s$	5 mm
Overall length L	54 mm
Flute length L_c	9 mm

Helix angle	30 degrees
Radius R	2.5 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	0.03×D for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	without
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------