

Garant
Diabolo solid carbide copy slot drill, TiAlN, Ø Dc × L1: 0,2X1,5 mm


Order data

Order number	207373 0,2X1,5
GTIN	4045197935908
Item class	11X

Description

Version:

GARANT Diabolo:

Special geometry, coating and carbide **for hard machining in the high-performance field.**
Suitable even for **machining electrolytic copper.**

Recess angle $\alpha = 16^\circ$.

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø: D₁ = 0 / -0.01 mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p!
values for:

copying: $a_p = 0.05 \times D \times a_{p, \text{korr}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)! e.g: $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

No. of teeth Z: 2

Helix angle: 25 degrees

No. of teeth Z: 2

Flute length L_c: 0.16 mm

Corner radius R₁: 0.1 mm

Overhang length L₁ incl. recess: 1.5 mm

Recess Ø D₁: 0.17 mm

Overall length L: 45 mm

Technical description

Correction factor a _{p, corr}	0.8
Corner radius R ₁	0.1 mm

Helix angle	25 degrees
Shank $\varnothing D_s$	4 mm
Overhang length L_1 incl. recess	1.5 mm
Feed f_z for copy milling in steel < 65 HRC	0.009 mm
Overall length L	45 mm
Cutting edge $\varnothing D_c$	0.2 mm
Recess $\varnothing D_1$	0.17 mm
Flute length L_c	0.16 mm
No. of teeth Z	2
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	0 / -0,005
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	red
Type of product	End mill