

**Garant**
**Diabolo solid carbide copy slot drill, TiAlN, Ø Dc × L1: 1X18 mm**

**Order data**

Order number	207373 1X18
GTIN	4045197936370
Item class	11X

**Description**
**Version:**
**GARANT Diabolo:**

Special geometry, coating and carbide **for hard machining in the high-performance field.**  
Suitable even for **machining electrolytic copper.**

Recess angle  $\alpha = 16^\circ$ .

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø: D<sub>1</sub> = 0 / -0.01 mm.**

**Note:**

At greater tool overhang lengths, use a reduced value for a<sub>p</sub>!  
values for:

copying:  $a_p = 0.05 \times D \times a_{p, \text{korr}}$

**To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)! e.g:  $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$**

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L<sub>c</sub>: 0.8 mm

Corner radius R<sub>1</sub>: 0.5 mm

Overhang length L<sub>1</sub> incl. recess: 18 mm

Recess Ø D<sub>1</sub>: 0.96 mm

Overall length L: 60 mm

**Technical description**

Overhang length L <sub>1</sub> incl. recess	18 mm
Flute length L <sub>c</sub>	0.8 mm

Helix angle	30 degrees
Correction factor $a_{p\text{ corr}}$	0.08
No. of teeth Z	2
Overall length L	60 mm
Shank $\varnothing D_s$	4 mm
Cutting edge $\varnothing D_c$	1 mm
Feed $f_z$ for copy milling in steel < 65 HRC	0.01 mm
Recess $\varnothing D_1$	0.96 mm
Corner radius $R_1$	0.5 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal $\varnothing$	0 / -0,005
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	red
Type of product	End mill