

Garant
Solid carbide ball nose slot drill, TiAlN, Ø DC: 10 mm

Order data

Order number	207381 10
GTIN	4045197551887
Item class	11X

Description
Version:

Tolerance: Radius contour = ± 0.01 mm.

No. of teeth Z: 3

Helix angle: 35 degrees

No. of teeth Z: 3

Flute length L_c : 19 mm

Overall length L: 72 mm

Shank $\varnothing D_s$: 10 mm

Feed f_z for side milling in steel < 500 N/mm²: 0.06 mm

Feed f_z for copy milling in steel < 500 N/mm²: 0.068 mm

Technical description

Cutting edge $\varnothing D_c$	10 mm
No. of teeth Z	3
Feed f_z for copy milling in steel < 500 N/mm ²	0.068 mm
Feed f_z for side milling in steel < 500 N/mm ²	0.06 mm
Shank $\varnothing D_s$	10 mm
Overall length L	72 mm
Flute length L_c	19 mm
Helix angle	35 degrees
Radius R	5 mm

Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.1×D for copy milling
Cutting width a_e for milling operation	0.5×D for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	without
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB