

Garant
Solid carbide ball nose slot drill, DLC, Ø f8 DC: 3 mm

Order data

Order number	207441 3
GTIN	4045197591036
Item class	11X

Description
Version:

With the latest generation of **DLC coating sp²**. For **high-performance milling of aluminium materials**. 4 centre cutting edges to the centre. Therefore can be used as a true **4-edge drill** at all depths of cut.

Tolerance: Radius contour = **±0.005 mm**.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c: 6 mm

Overhang length L₁ incl. recess: 16 mm

Recess Ø D₁: 2.7 mm

Overall length L: 50 mm

Shank Ø D_s: 3 mm

Technical description

Feed f _z for copy milling in cast aluminium	0.03 mm
Recess Ø D ₁	2.7 mm
No. of teeth Z	4
Cutting edge Ø D _c	3 mm
Overhang length L ₁ incl. recess	16 mm
Shank Ø D _s	3 mm
Overall length L	50 mm

Flute length L_c	6 mm
Helix angle	45 degrees
Radius R	1.5 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.1 \times D$ for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------