

Garant
Solid carbide ball nose slot drill, DLC, Ø f8 DC: 4 mm

Order data

Order number	207441 4
GTIN	4045197591043
Item class	11X

Description
Version:

With the latest generation of **DLC coating sp²**. For **high-performance milling of aluminium materials**. 4 centre cutting edges to the centre. Therefore can be used as a true **4-edge drill** at all depths of cut.

Tolerance: Radius contour = **±0.005 mm**.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c: 7 mm

Overhang length L₁ incl. recess: 17 mm

Recess Ø D₁: 3.7 mm

Overall length L: 54 mm

Shank Ø D_s: 4 mm

Technical description

Overhang length L ₁ incl. recess	17 mm
No. of teeth Z	4
Feed f _z for copy milling in cast aluminium	0.03 mm
Recess Ø D ₁	3.7 mm
Cutting edge Ø D _c	4 mm
Shank Ø D _s	4 mm
Overall length L	54 mm

Flute length L_c	7 mm
Helix angle	45 degrees
Radius R	2 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.1 \times D$ for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------