

Garant
Solid carbide ball nose slot drill, DLC, Ø f8 DC: 8 mm

Order data

Order number	207441 8
GTIN	4045197591074
Item class	11X

Description
Version:

With the latest generation of **DLC coating sp²**. For **high-performance milling of aluminium materials**. 4 centre cutting edges to the centre. Therefore can be used as a true **4-edge drill** at all depths of cut.

Tolerance: Radius contour = **±0.005 mm**.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c: 12 mm

Overhang length L₁ incl. recess: 27 mm

Recess Ø D₁: 7.5 mm

Overall length L: 59 mm

Shank Ø D_s: 8 mm

Technical description

Recess Ø D ₁	7.5 mm
No. of teeth Z	4
Cutting edge Ø D _c	8 mm
Overhang length L ₁ incl. recess	27 mm
Feed f _z for copy milling in cast aluminium	0.06 mm
Shank Ø D _s	8 mm
Overall length L	59 mm

Flute length L_c	12 mm
Helix angle	45 degrees
Radius R	4 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.1 \times D$ for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Colour ring	yellow
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB