

Garant
Diabolo solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS: 2 mm

Order data

Order number	207472 2
GTIN	4045197600509
Item class	11X

Description
Version:
GARANT Diabolo:

Special geometry, newly developed coating and carbide for hard machining. 4 centre cutting edges to the centre. Therefore can be used as a true **4-edge drill** at all depths of cut.

Tolerance: Radius contour = **±0.005 mm.**

No. of teeth Z: 4

Helix angle: 30 degrees

No. of teeth Z: 4

Flute length L_c : 4 mm

Overall length L: 50 mm

Shank Ø D_s : 3 mm

Feed f_z for side milling in steel < 65 HRC: 0.005 mm

Feed f_z for copy milling in steel < 65 HRC: 0.005 mm

Technical description

Feed f_z for side milling in steel < 65 HRC	0.005 mm
Feed f_z for copy milling in steel < 65 HRC	0.005 mm
No. of teeth Z	4
Cutting edge Ø D_c	2 mm
Shank Ø D_s	3 mm
Overall length L	50 mm
Flute length L_c	4 mm

Helix angle	30 degrees
Radius R	1 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Cutting width a_e for milling operation	0.2×D for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	red
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------