

## Garant

### Solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS: 8 mm



#### Order data

Order number	207477 8
GTIN	4045197455482
Item class	11X

#### Description

##### Version:

**Special geometry** and **coating** for machining **stainless and acid-resistant steels**. 4 end faces up to the centre. Therefore can be used as a true **4-edge drill** at all depths of cut.

Tolerance: Radius contour =  $\pm 0.005$  mm.

##### Note:

**New generation available!** Successor product is No. 207473.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length  $L_c$ : 12 mm

Overall length L: 58 mm

Shank  $\varnothing D_s$ : 8 mm

Feed  $f_z$  for side milling in INOX < 900 N/mm<sup>2</sup>: 0.025 mm

Feed  $f_z$  for copy milling in stainless steel < 900 N/mm<sup>2</sup>: 0.028 mm

#### Technical description

Feed $f_z$ for side milling in INOX < 900 N/mm <sup>2</sup>	0.025 mm
No. of teeth Z	4
Feed $f_z$ for copy milling in stainless steel < 900 N/mm <sup>2</sup>	0.028 mm
Cutting edge $\varnothing D_c$	8 mm
Shank $\varnothing D_s$	8 mm
Overall length L	58 mm

Flute length $L_c$	12 mm
Helix angle	45 degrees
Radius R	4 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.05×D for copy milling
Cutting width $a_e$ for milling operation	0.5×D for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB