

Garant
Solid carbide engraving cutter 60°, uncoated, Ø h6 DC: 6 mm

Order data

Order number	208040 6
GTIN	4045197129079
Item class	11X

Description
Application:

For engraving contours.

Note:

f_z for $a_e = 1.0 \times D$

Through-coolant: no

No. of teeth Z: 1

Shank: DIN 6535 HA to h6

No. of teeth Z: 1

Flute length L_c : 20 mm

Overall length L: 54 mm

Shank $\varnothing D_s$: 6 mm

Feed f_z in steel < 900 N/mm²: 0.03 mm

Technical description

Cutting edge $\varnothing D_c$	6 mm
Feed f_z in steel < 900 N/mm ²	0.03 mm
No. of teeth Z	1
Shank $\varnothing D_s$	6 mm
Flute length L_c	20 mm
Overall length L	54 mm
Shank	DIN 6535 HA to h6
Corner chamfer angle	60 degrees

Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 20 mm

SZ2025 20