

**Garant**
**Solid carbide chamfering cutter 120°, uncoated, Ø e8 DC: 10 mm**

**Order data**

Order number	208080 10
GTIN	4045197129208
Item class	11X

**Description**
**Version:**

**Tolerance:** Point angle  $\pm 1^\circ$ .

**Application:**

- **Slot milling**
- **Countersinking**
- **Milling**
- **Can also be used as a NC spotting drill.**

**Note:**

For **HB** shanks use order **No. 208081**.

HB shanks are available at the same price as HA.

No. of teeth Z: 2

Shank: DIN 6535 HB to h6

Chamfer mill: 60 degrees

No. of teeth Z: 2

Flute length  $L_c$ : 22 mm

Overall length L: 72 mm

Shank  $\varnothing D_s$ : 10 mm

Feed  $f_z$  for side milling in steel  $< 900 \text{ N/mm}^2$ : 0.05 mm

**Technical description**

No. of teeth Z	2
Cutting edge $\varnothing D_c$	10 mm
Feed $f_z$ for side milling in steel $< 900 \text{ N/mm}^2$	0.05 mm
Shank $\varnothing D_s$	10 mm

Flute length $L_c$	22 mm
Overall length L	72 mm
Shank	DIN 6535 HB to h6
Corner chamfer angle	30 degrees
Chamfer mill	60 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	e8
Helix angle	30 degrees
Cutting width $a_e$ for milling operation	0.5×D for side milling
Countersink tip angle	120 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

### Services

Shank grinding Type HB	129100 HB
------------------------	-----------