

**Garant**
**Solid carbide deburrer 120°, TiAlN, Ø h6 DC: 3 mm**

**Order data**

Order number	208092 3
GTIN	4045197858481
Item class	11X

**Description**
**Version:**

With special flute geometry for smooth cutting.

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

**Application:**

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 3

Shank: DIN 6535 HA with h6

Chamfer mill: 60 degrees

No. of teeth Z: 3

Flute length  $L_c$ : 0.85 mm

Dimension S: 1.6 mm

Overall length L: 50 mm

Shank Ø  $D_s$ : 3 mm

Feed  $f_z$  in steel < 900 N/mm<sup>2</sup>: 0.01 mm

**Technical description**

Feed $f_z$ in steel < 900 N/mm <sup>2</sup>	0.01 mm
Shank Ø $D_s$	3 mm
Flute length $L_c$	0.85 mm
Dimension S	1.6 mm
Cutting edge Ø $D_c$	3 mm
Shank	DIN 6535 HA with h6

Overall length L	50 mm
No. of teeth Z	3
Corner chamfer angle	30 degrees
Chamfer mill	60 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	120 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill