

Garant
Solid carbide deburrer 90°, uncoated, Ø h6 DC: 6 mm

Order data

Order number	208095 6
GTIN	4045197858580
Item class	11X

Description
Version:

With special flute geometry for smooth cutting.

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HA with h6

Chamfer mill: 45 degrees

No. of teeth Z: 4

Dimension S: 4.2 mm

Overall length L: 57 mm

Shank Ø D_s: 6 mm

Feed f_z in steel < 900 N/mm²: 0.03 mm

Technical description

Shank	DIN 6535 HA with h6
Overall length L	57 mm
Shank Ø D _s	6 mm
No. of teeth Z	4
Cutting edge Ø D _c	6 mm
Feed f _z in steel < 900 N/mm ²	0.03 mm
Dimension S	4.2 mm

Corner chamfer angle	45 degrees
Chamfer mill	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	90 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------