


Solid carbide deburrer 90°, uncoated, Ø h6 DC: 10 mm

Order data

| | |
|--------------|---------------|
| Order number | 208097 10 |
| GTIN | 4045197858689 |
| Item class | 12X |

Description
Version:

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HA with h6

Chamfer mill: 45 degrees

No. of teeth Z: 4

Flute length L_c: 7 mm

Dimension S: 7 mm

Overall length L: 67 mm

Shank Ø D_s: 10 mm

Feed f_z in steel < 900 N/mm²: 0.05 mm

Technical description

| | |
|--|---------------------|
| Flute length L _c | 7 mm |
| Shank | DIN 6535 HA with h6 |
| Overall length L | 67 mm |
| No. of teeth Z | 4 |
| Shank Ø D _s | 10 mm |
| Dimension S | 7 mm |
| Feed f _z in steel < 900 N/mm ² | 0.05 mm |

| | |
|---------------------------------|-------------------------|
| Cutting edge $\varnothing D_c$ | 10 mm |
| Corner chamfer angle | 45 degrees |
| Chamfer mill | 45 degrees |
| Coating | uncoated |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | N |
| Tolerance nominal \varnothing | h6 |
| Direction of infeed | horizontal and oblique |
| Countersink tip angle | 90 degrees |
| Through-coolant | no |
| Shank tolerance | h6 |
| Colour ring | without |
| Type of product | End mill |

Services

| | |
|------------------------|-----------|
| Shank grinding Type HB | 129100 HB |
|------------------------|-----------|