


**Solid carbide deburrer 90°, uncoated, Ø h6 DC: 3 mm**

**Order data**

Order number	208097 3
GTIN	4045197858641
Item class	12X

**Description**
**Version:**

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

**Application:**

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 3

Shank: DIN 6535 HA with h6

Chamfer mill: 45 degrees

No. of teeth Z: 3

Dimension S: 2.1 mm

Overall length L: 38 mm

Shank Ø D<sub>s</sub>: 3 mm

Feed f<sub>z</sub> in steel < 900 N/mm<sup>2</sup>: 0.01 mm

**Technical description**

Feed f <sub>z</sub> in steel < 900 N/mm <sup>2</sup>	0.01 mm
Shank	DIN 6535 HA with h6
Dimension S	2.1 mm
No. of teeth Z	3
Cutting edge Ø D <sub>c</sub>	3 mm
Shank Ø D <sub>s</sub>	3 mm
Overall length L	38 mm

Corner chamfer angle	45 degrees
Chamfer mill	45 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	90 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill