

Garant

Solid carbide deburrer 60°, uncoated, Ø h6 DC: 4 mm



Order data

Order number	208125 4
GTIN	4045197858894
Item class	11X

Description

Version:

With special flute geometry for smooth cutting.

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HA with h6

Chamfer mill: 30 degrees

No. of teeth Z: 4

Dimension S: 3.9 mm

Overall length L: 54 mm

Shank Ø D_s: 4 mm

Feed f_z in steel < 900 N/mm²: 0.02 mm

Technical description

Overall length L	54 mm
Shank	DIN 6535 HA with h6
Shank Ø D _s	4 mm
Cutting edge Ø D _c	4 mm
Dimension S	3.9 mm
Feed f _z in steel < 900 N/mm ²	0.02 mm
No. of teeth Z	4

Corner chamfer angle	60 degrees
Chamfer mill	30 degrees
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill