


Solid carbide deburrer 60°, TiAlN, Ø h6 DC: 2 mm

Order data

Order number	208137 2
GTIN	4045197859112
Item class	12X

Description
Version:

Tolerance: **Dimension S = ± 0.1 mm, point angle ± 10 arc minutes.**

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 3

Shank: DIN 6535 HA with h6

Chamfer mill: 30 degrees

No. of teeth Z: 3

Dimension S: 1.9 mm

Overall length L: 38 mm

Shank $\varnothing D_s$: 3 mm

Feed f_z in steel < 900 N/mm²: 0.01 mm

Technical description

Cutting edge $\varnothing D_c$	2 mm
Dimension S	1.9 mm
Shank	DIN 6535 HA with h6
Feed f_z in steel < 900 N/mm ²	0.01 mm
Overall length L	38 mm
No. of teeth Z	3
Shank $\varnothing D_s$	3 mm

Corner chamfer angle	60 degrees
Chamfer mill	30 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	60 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill