


Solid carbide deburrer 60°, TiAlN, Ø h6 DC: 3 mm

Order data

| | |
|--------------|---------------|
| Order number | 208137 3 |
| GTIN | 4045197859129 |
| Item class | 12X |

Description
Version:

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

Application:

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 3

Shank: DIN 6535 HA with h6

Chamfer mill: 30 degrees

No. of teeth Z: 3

Flute length L_c : 2.9 mm

Dimension S: 2.9 mm

Overall length L: 38 mm

Shank Ø D_s : 3 mm

Feed f_z in steel < 900 N/mm²: 0.01 mm

Technical description

| | |
|---|---------------------|
| Feed f_z in steel < 900 N/mm ² | 0.01 mm |
| Shank | DIN 6535 HA with h6 |
| No. of teeth Z | 3 |
| Cutting edge Ø D_c | 3 mm |
| Overall length L | 38 mm |
| Shank Ø D_s | 3 mm |
| Flute length L_c | 2.9 mm |

| | |
|---------------------------------|-------------------------|
| Dimension S | 2.9 mm |
| Corner chamfer angle | 60 degrees |
| Chamfer mill | 30 degrees |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Type | N |
| Tolerance nominal \varnothing | h6 |
| Direction of infeed | horizontal and oblique |
| Countersink tip angle | 60 degrees |
| Through-coolant | no |
| Shank tolerance | h6 |
| Colour ring | without |
| Type of product | End mill |