

**Garant**
**Solid carbide deburrer 30°, TiAlN, Ø h6 DC: 6 mm**

**Order data**

Order number	208152 6
GTIN	4045197859303
Item class	11X

**Description**
**Version:**

Tolerance: **Dimension S = ±0.1 mm, point angle ±10 arc minutes.**

With special flute geometry for smooth cutting.

**Application:**

Perfectly suitable for **chamfering** and **deburring** component edges and for **contouring applications**.

No. of teeth Z: 4

Shank: DIN 6535 HA with h6

Chamfer mill: 15 degrees

No. of teeth Z: 4

Dimension S: 11.2 mm

Overall length L: 57 mm

Shank Ø D<sub>s</sub>: 6 mm

Feed f<sub>z</sub> in steel < 900 N/mm<sup>2</sup>: 0.03 mm

**Technical description**

Dimension S	11.2 mm
Cutting edge Ø D <sub>c</sub>	6 mm
Shank Ø D <sub>s</sub>	6 mm
No. of teeth Z	4
Overall length L	57 mm
Shank	DIN 6535 HA with h6
Feed f <sub>z</sub> in steel < 900 N/mm <sup>2</sup>	0.03 mm

Corner chamfer angle	75 degrees
Chamfer mill	15 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	h6
Direction of infeed	horizontal and oblique
Countersink tip angle	30 degrees
Through-coolant	no
Shank tolerance	h6
Colour ring	without
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------