

Garant

Solid carbide front / back deburring cutter, TiAlN, Ø DC: 11,8 mm



Order data

Order number	208180 11,8
GTIN	4045197465603
Item class	11X

Description

Version:

Extra long shank.

Double ground head **with 45° angle.**

Application:

For **front** and **back deburring** and **chamfering** even where access is difficult.

Particularly suitable for **contouring applications.**

No. of teeth Z: 4

Chamfer mill: backwards and forwards 45

$L_2 +0,5$: 6 mm

$L_4 +0,5$: 94 mm

Overall length L: 100 mm

Shape: flat

Shank Ø D_s : 6 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.017 mm

Technical description

Shape	flat
Feed f_z for side milling in steel < 900 N/mm ²	0.017 mm
$L_2 +0,5$	6 mm
$L_4 +0,5$	94 mm
Cutting edge Ø D_c	11.8 mm
No. of teeth Z	4
Shank Ø D_s	6 mm

Overall length L	100 mm
Chamfer mill	backwards and forwards 45
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	± 0.05
Countersink tip angle	90 degrees
Cutting width a_e for milling operation	$0.25 \times L_2$ for side milling
Shank	DIN 6535 HA to h6
Shank tolerance	h6
Colour ring	without
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------