

Garant
Solid carbide front / back deburring cutter, TiAlN, Ø DC: 5 mm

Order data

Order number	208180 5
GTIN	4045197198372
Item class	11X

Description
Version:
Extra long shank.

Double ground head **with 45° angle.**

Application:

For **front** and **back deburring** and **chamfering** even where access is difficult.

Particularly suitable for **contouring applications.**

No. of teeth Z: 4

Chamfer mill: backwards and forwards 45

$L_2 +0,5$: 3 mm

$L_4 +0,5$: 15 mm

$\varnothing D_1 +0.05$: 3.9 mm

Overall length L: 75 mm

Shape: pointed

Shank $\varnothing D_s$: 5 mm

Technical description

$L_2 +0,5$	3 mm
$L_4 +0,5$	15 mm
No. of teeth Z	4
$\varnothing D_1 +0.05$	3.9 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.01 mm
Cutting edge $\varnothing D_c$	5 mm
Shape	pointed

Shank $\varnothing D_s$	5 mm
Overall length L	75 mm
Chamfer mill	backwards and forwards 45
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	± 0.05
Countersink tip angle	90 degrees
Cutting width a_e for milling operation	$0.25 \times L_2$ for side milling
Shank	DIN 6535 HA to h6
Shank tolerance	h6
Colour ring	without
Type of product	End mill