

Garant
Solid carbide router cutter compacting cut coarse, uncoated, Ø h10 DC: 6 mm

Order data

Order number	209420 6
GTIN	4045197477712
Item class	11X

Description
Version:

High performance diamond-pattern teeth for efficient machining of fibre-reinforced composites. For slot cutting in the roughing range.

Compacting cut, the material is pushed down on to the substrate. Highly suitable for thin materials.

Flute length L_c : 19 mm

Overall length L : 60 mm

Shank $\varnothing D_s$: 6 mm

Feed f for side milling in POM GF25: 0.18 mm/rev.

Feed f for side milling in PEEK CF30: 0.12 mm/rev.

Technical description

No. of teeth Z	2
Feed f for side milling in POM GF25	0.18 mm/rev.
Cutting edge $\varnothing D_c$	6 mm
Feed f for side milling in PEEK CF30	0.12 mm/rev.
Shank $\varnothing D_s$	6 mm
Flute length L_c	19 mm
Overall length L	60 mm
Corner chamfer angle	90 degrees
Coating	uncoated
Toothing grit designation	coarse

Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	staggered teeth
Type	W
Tolerance nominal \varnothing	h10
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.5×D for side milling
Shank	DIN 6535 HA with h6
Through-coolant	no
Colour ring	yellow
Shank tolerance	h6
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB