

## Garant

### Solid carbide router cutter compacting cut medium, uncoated, Ø h10 DC: 10 mm



#### Order data

Order number	209425 10
GTIN	4045197477682
Item class	11X

#### Description

##### Version:

**High performance diamond-pattern teeth** for efficient machining of fibre-reinforced composites. For slot cutting in the roughing range.

**Compacting cut**, the material is pushed down on to the substrate. Highly suitable for thin materials.

Flute length  $L_c$ : 25 mm

Overall length L: 72 mm

Shank  $\varnothing D_s$ : 10 mm

Feed f for side milling in POM GF25: 0.3 mm/rev.

Feed f for side milling in PEEK CF30: 0.2 mm/rev.

#### Technical description

Feed f for side milling in PEEK CF30	0.2 mm/rev.
No. of teeth Z	3
Feed f for side milling in POM GF25	0.3 mm/rev.
Cutting edge $\varnothing D_c$	10 mm
Shank $\varnothing D_s$	10 mm
Flute length $L_c$	25 mm
Overall length L	72 mm
Corner chamfer angle	90 degrees
Coating	uncoated

Toothing grit designation	medium
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	staggered teeth
Type	W
Tolerance nominal $\varnothing$	h10
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.5×D for side milling
Shank	DIN 6535 HA with h6
Through-coolant	no
Colour ring	yellow
Shank tolerance	h6
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB