

Garant

Solid carbide router cutter dragging cut medium, uncoated, Ø h10 DC: 4 mm



Order data

| | |
|--------------|---------------|
| Order number | 209460 4 |
| GTIN | 4045197510341 |
| Item class | 11X |

Description

Version:

High performance diamond-pattern teeth for efficient machining of fibre-reinforced composites. For slot cutting in the roughing range. The cutters have a **precise radius contour in the radius area**. This enables outstanding results when copy milling.

Flute length L_c : 19 mm

Overall length L : 50 mm

Shank $\varnothing D_s$: 4 mm

Feed f for side milling in POM GF25: 0.1 mm/rev.

Feed f for side milling in PEEK CF30: 0.07 mm/rev.

Technical description

| | |
|--|--------------|
| Cutting edge $\varnothing D_c$ | 4 mm |
| Feed f for side milling in POM GF25 | 0.1 mm/rev. |
| Feed f for side milling in PEEK CF30 | 0.07 mm/rev. |
| No. of teeth Z | 4 |
| Shank $\varnothing D_s$ | 4 mm |
| Flute length L_c | 19 mm |
| Overall length L | 50 mm |
| Corner rounding r_v | 2 mm |
| Coating | uncoated |
| Toothing grit designation | medium |

| | |
|---|----------------------------------|
| Tool material | Solid carbide |
| Standard | Manufacturer's standard |
| Milling profile | staggered teeth |
| Type | W |
| Tolerance nominal \varnothing | h10 |
| Direction of infeed | horizontal, oblique and vertical |
| Cutting width a_e for milling operation | 0.5×D for side milling |
| Shank | DIN 6535 HA with h6 |
| Through-coolant | no |
| Colour ring | yellow |
| Shank tolerance | h6 |
| Type of product | End mill |

Services

| | |
|------------------------|-------------|
| Shank recess Type FRST | 209900 FRST |
|------------------------|-------------|