

Solid carbide router cutter compacting cut fine, Diamond, Ø h10 DC: 6 mm



Order data

Order number	209512 6
GTIN	4045197509826
Item class	11Y

Description

Version:

High performance diamond-pattern cut for efficient roughing of fibre-reinforced composites.

Balance quality with shank: G 2.5 with HA

Flute length L_c : 19 mm Overall length L: 60 mm Shank \emptyset D_s: 6 mm

Feed f for side milling in GRP CRP: 0.28 mm/rev.

Technical description

No. of teeth Z	2
Cutting edge Ø D _C	6 mm
Shank Ø D _s	6 mm
Overall length L	60 mm
Flute length L _c	19 mm
Balance quality with shank	G 2.5 with HA
Feed f for side milling in GRP CRP	0.28 mm/rev.
Corner chamfer angle	90 degrees
Coating	Diamond
Toothing grit designation	fine
Tool material	Solid carbide
Standard	Manufacturer's standard



Milling profile	staggered teeth
Tolerance nominal Ø	h10
Direction of infeed	horizontal, oblique and vertical
Cutting width a _e for milling operation	0.5×D for side milling
Shank	DIN 6535 HA with h6
Through-coolant	no
Colour ring	black
Shank tolerance	h6
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------